



ENEOS ULTRA-VC 0W-20

Tailor-made ultra-low viscosity synthetic technology engineered for Volvo's latest engines

ENEOS ULTRA-VC 0W-20, a cutting-edge fully synthetic engine oil meticulously engineered to meet the stringent ACEA C5 and Volvo Cars VCC RBS0-2AE specifications. Designed as a tailor-made solution for Volvo's modern vehicles, this ultra-low viscosity oil boasts an advanced formulation utilizing premium synthetic base oils and a dedicated additive package. With its low-friction additives and high viscosity index, ENEOS ULTRA-VC 0W-20 delivers exceptional fuel efficiency while ensuring optimal lubrication, reduced emissions, and enhanced engine life – keeping pace with the evolving demands of Volvo's newest powertrains requiring SAE 0W-20 viscosity grade. This unique product exemplifies ENEOS's commitment to developing innovative, manufacturer-specific lubricants that cater to the cutting-edge needs of modern automotive engineering.

SPECIAL FEATURES

1. Enhanced Fuel Economy and Low Emission

This low viscosity engine oil is made with highest performance fully-synthetic base stock with carefully selected additive blend to increase engine efficiency and help saving on fuel costs, exceeding the industry standards for fuel economy, while reducing harmful exhaust emission. Designed to meet latest, most stringent emission reduction requirements.

2. Extended engine life

The high-quality synthetic base oils and dedicated additive packages in these 0W-20 oils help protect critical engine components, prolonging engine life.

3. Superior cold-start Protection

The unique formulation of ENEOS ULTRA-VC 0W-20 provides unsurpassed protection at cold engine start even in the coldest environment conditions. This protection is fast and substantially reduces engine wear. The low viscosity formulation guarantees superb overall and long lasting lubrication and engine cleanliness in all driving styles and conditions through outstanding thermal stability.

PERFORMANCE LEVELS

- ACEA C5
- Volvo Cars VCC RBS0-2AE

APPLICABLE VEHICLES

Recommended for Volvo vehicles requiring VCC RBS0-2AE specification engine oil.

PACK SIZES

1L, 4L, 20L, 60L, 208L

TYPICAL PROPERTIES

SAE viscosity grade	0W-20
Density (15°C), g/cm ³	0.8432
Flash point (COC), °C	230
Kinematic viscosity	
(40°C), mm ² /s	46.31
(100°C), mm ² /s	9.2
Viscosity index	185
Pour point, °C	-48.0
TAN mgKOH/g	1.71
TBN mgKOH/g (HClO ₄)	7.68

Note: The typical properties may be changed without notice.

(April 2024)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.